imagePROGRAF TX-2000

A PRECISE, PRODUCTIVE AND HIGH-PERFORMANCE LARGE-FORMAT INKJET PRINTER, WITH INNOVATIVE FEATURES.





- Unparalleled productivity thanks to new print head and continuous printing capability
- Supreme print quality and class-leading precision from LUCIA TD ink
- Unique dual-roll feeding on a 24-inch CAD, GIS & Poster inkjet large format printer
- Bold, vivid colours on both plain media and economical uncoated paper
- Simple roll loading, seamless touchscreen control and printing direct from USB
- Conveniently print to any network-connected TX-Series unit with a Universal Driver
- Neat compact chassis allows the TX-2000 to fit into compact environments
- Steadfast reliability, with maximum uptime and robust security
- Engineered for weather-resistant printed output
- Value-added software improves large format printing workflows

A versatile 24-inch inkjet for large-format CAD, GIS and Poster printing, delivering enviable efficiency, pinpoint accuracy, superb security standards and low running costs.



PRODUCT RANGE



Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-2000

Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)

Printer unit with basket open and printer stand: 1110 x 984 x 1168mm (Basket Open) Weight: 91 kg (including Roll Holder)

imagePROGRAF TX-Series Printer Driver, Print

Other software available as Download from Web

At sleep mode (using wired LAN): 3.6 W or less

At the power off: 0.3 W or less Default setting for the time to enter the Sleep mode:

Operation: 51dB(A) or less (Plain paper, line drawing,

At sleep mode (using all ports): 3.6 W or less <EU only - data for ErP Lot 26>

15 - 30°C, 10 - 80 % (Condensation free)

Europe: CE mark Russia: EAC, Other Countries: CB certification

ENERGY STAR (WW), RoHS directive, IT ECO

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3'

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3° Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet

Plug-In for Office, Quick Utility Toolbox and

Input Power: AC 100-240 V (50-60 Hz) Power consumption (using wired LAN):

<EU only - data for ErP Lot 26>

Stand by : 35dB(A) or less (Measured on ISO7779 standard)

PosterArtist Lite

91 W or less

standard mode)

Declaration (Europe)

TECHNOLOGY

Printer Type

Print Technology

Number of Nozzles

Print Resolution Nozzle Pitch

Guaranteed Minimum Line Width

Line Accuracy Ink Droplet Size Ink Capacity

Ink Type

OS Compatability

Printer Languages

Standard Interfaces

WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)

MEMORY

Standard memory **Expansion slot**

HARD DISK

PAPER HANDLING Media Width

Media Thickness Minimum Printable Length

Maximum Printable Length

Maximum Media Roll

Canon Bubbleiet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each

5 Colour - 24"/609.6mm

2,400 x 1,200 dpi

1,200 x 2 includes Non-firing nozzle detection and compensation system

0.02 mm

±0.1 % or less

5 Picoliter per colour

Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y)

Sales Ink: 160ml/330ml/700ml

Pigment ink: 5 colour MBK/BK/C/M/Y

Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2,

Server 2012/R2 Apple Macintosh: OSX 10.7.5 ~ 10.11

SGRaster (Swift Graphic Raster) HP-GL/2, HP RTL, PDF, JPEG - for details check

specifications

USB B Port: Type: Built in (Hi-Speed USB) Mode: Full Speed (12 Mbit/sec) High Speed (480 Mbit/sec), Bulk transfer

Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T

IEEE 802.3u 100base-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation

IEEE 802.3x Full Duplex

Protocol: SNMP (Canon-MIB), HTTP, TCP/IP (IPv4/IPv6), ftp

Wireless LAN:

IEEE802.11n/IEEE802.11g/IEEE802.11b

128GB (Physical memory 2GB)

500GB (Encrypted)

Roll paper: 8"/203.2mm - 24"/609.6mm Cut sheet: 8"/203.2mm - 24"/609.6mm 0.07 - 0.8mm

203mm Roll Paper: 18 m

(varies according to the OS and application) Cut Sheet: 1.6m

170 mm

Paper Feed Method

Borderless Printing Width

[Recommended] 515mm(JIS B2), 594mm (ISO AI), 10", 14", 17", 24", [Printable] 257mm (JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 8", 12", 16", 20", 300mm, 500mm, (Roll Only) 600mm

DIMENSIONS AND WEIGHT Physical Dimensions -

 $(W \times D \times H)$

Software Included

POWER AND OPERATING REQUIREMENTS

Power Supply

Operating Environment

Noise Level (Approx.)

Regulations

Enviroment Certificates

WHAT'S INCLUDED What's in the Box?

OPTIONS Optional Items

CONSUMABLES

User Replaceable Items

Print Head: PF-06

Printer Stand: SD-21

Roll Unit: RU-22 2/3" Roll Holder: RH2-27

Stacker: SS-21

Ink Tanks: PFI-110(160ml), PFI-310(330ml), PFI-710(700ml) Maintenance Cartridge: MC-30 Cutter Blade: CT-07

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and R. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









Canon Inc.

Canon Europe

canon-europe.com

English edition © Canon Europa N.V., 2017