

# imagePROGRAF GP-200

## MAXIMISE YOUR PRINT MARKETING POTENTIAL WITH VIBRANT, EYE-CATCHING POSTER PRODUCTION

A compact, large format printer with newly developed fluorescent pigment ink for easy, high impact poster design, ideal for maximising sales and profits from retail and hospitality marketing.



- **Vivid colours**

Print eye-catching posters every time with advanced spot colour accuracy and fluorescent colour expression using newly developed fluorescent pink ink

- **Easy poster creation**

Create attractive and impactful marketing materials with PosterArtist 3.4, featuring new templates and built-in stock photo service, helping you produce stylish posters for any purpose

- **Professional finish**

High-precision paper edge detection supports free-size borderless printing for all paper roll sizes, making it easy to create borderless posters without cutting a printout

- **Direct to print**

Built in HDD allows for convenient and efficient printing of the saved data, also PDF and JPEG file can be printed from a USB memory without connecting to a PC

- **Compact design**

Maximise available office space with a small footprint printer that fits flat against the wall to offer full front usability, perfect for smaller offices

- **Security assured**

Have complete confidence in the security of your printouts with PIN-accessed Security Print feature

### PRODUCT RANGE



imagePROGRAF GP-300



imagePROGRAF GP-4000



imagePROGRAF GP-2000

**Canon**

---

# TECHNICAL SPECIFICATIONS

# imagePROGRAF GP-200

## TECHNOLOGY

<b>Printer Type</b>	6 Colour 24"
<b>Print Technology</b>	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
<b>Print Resolution</b>	2,400 x 1,200 dpi
<b>Number of Nozzles</b>	Total : 15,360 nozzles MBK, BK, C, M, Y, FP : 2,560 nozzles each
<b>Line Accuracy</b>	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
<b>Nozzle Pitch</b>	1,200 dpi x 2 includes Non-firing nozzle detection and compensation system
<b>Ink Droplet Size</b>	minimum 5 pl per colour
<b>Ink Capacity</b>	Bundled Starter Ink : 90 ml (MBK, BK, C, M, Y, FP) Sales Ink : 130 ml, 300 ml
<b>Ink Type</b>	Pigment inks : 6 colour MBK, BK, C, M, Y, FP
<b>OS Compatibility</b>	Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10 Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11
<b>Printer Languages</b>	PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)
<b>Standard Interfaces</b>	USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in Hi-Speed USB Ethernet : IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T / Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN : IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN

## MEMORY

<b>Standard memory</b>	2GB
<b>Expansion slot : No</b>	
<b>Hard Drive</b>	500GB

## PRINTING SPEED

<b>Poster:</b>	
<b>Plain Paper (A1)</b>	0:25 (Fast) 0:44 (Standard)
<b>Heavy coated Paper (A1)</b>	0:55 (Fast) 1:22 (Standard)
<b>Glossy photo Paper (A1)</b>	3:28 (Standard) 5:18 (High Quality)

## MEDIA HANDLING

<b>Media Feed and Output</b>	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)
<b>Media Width</b>	Roll paper : 203.2 mm - 610 mm Cut sheet : 203.2 mm - 610 mm
<b>Media Thickness</b>	Roll/Cut : 0.07 mm - 0.8 mm
<b>Minimum Printable Length</b>	Roll paper : 203.2 mm Cut sheet : 279.4 mm
<b>Maximum Printable Length</b>	Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m
<b>Maximum Media Roll Diameter</b>	150 mm
<b>Media Core Size</b>	Internal diameter of roll core : 2"/3"
<b>Margins Recommended area</b>	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm
<b>Margins Printable area</b>	Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm
<b>Media Feed Capacity</b>	Roll Paper : 1 roll Cut Sheet : 1 sheet

## Borderless Printing Width (Roll Only)

[Recommended] 515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24"  
[Printable] 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 8", 12", 15", 16", 18", 20", 22", 300 mm, 500 mm, 600 mm, and custom roll width (203.2 - 610 mm)

## Maximum number of delivered prints

Standard position of the basket : 1 sheet

## DIMENSIONS AND WEIGHT

### Physical Dimensions WxDxH (mm) and Weight (Kg)

982 x 870 x 1060 mm (Basket Open)  
982 x 757 x 1060 mm (Basket Closed)  
50 kg (Main Unit + Stand + Basket, including Roll Holder Set, excluding ink and print head)

### Packaged Dimensions WxDxH (mm) and Weight (Kg)

Printer (Main unit with pallet) : 1152 x 913 x 705 mm  
69 kg  
Stand + Basket : 1055 x 824 x 268 mm  
16 kg

## POWER AND OPERATING REQUIREMENTS

### Power Supply

AC 100-240V (50-60Hz)

### Power Consumption

Operation : 71 W or less  
Sleep mode : 2.1 W or less  
Default setting for the time to enter the Sleep mode : Approx. 5 Minutes  
Power off : 0.3 W or less

### Operating Environment

Temperature : 15-30°C, Humidity : 10-80% RH (no dew condensation)

### Acoustic Noise (Power/Pressure)

Pressure  
Operation : 49 dB (A)  
(Plain paper, Standard mode, Poster)  
(Measured on ISO7779 standard)  
Standby : 35 dB (A) or less  
Power  
Operation : 6.7 Bels  
(Plain paper, Standard mode, Poster)  
(Measured on ISO7779 standard)

### Regulations

Europe : CE mark,  
Other Countries : CB certification

### Environment Certificates

TUV, CB

## WHAT'S INCLUDED

### What's in the Box?

Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Printer Stand Setup Guide, Quick Guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet

### Software Included

imagePROGRAF GP Printer Driver and PosterArtist Lite  
Other software available as Download from Web.

## OPTIONS

### Optional Items

2/3" Roll Holder : RH2-28  
Printer Stand : SD-24

## CONSUMABLES

### User Replaceable Items

Ink Tank : PFI-120 (130ml), PFI-320 (300ml)  
Print Head : PF-07  
Cutter Blade : CT-08  
Maintenance Cartridge : MC-31

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

