imagePROGRAF PRO-6000

LARGE FORMAT PHOTOGRAPHIC AND ART PRINTING HAS NEVER BEEN SO IMPRESSIVE.

The 60-inch large format printer in a league of its own – with peerless print quality, productive output speeds and supreme reliability.







KEY FEATURE

- Class-leading print quality for a 60-inch model, with LUCIA PRO 12-colour ink system
- Productive print speeds realized by the 1.28-inchwide print head
- Efficient workflow enabled by dual-roll unit, offering continuous feeding and automatic paper take-up
- Space-saving compact and attractive body
- Simplified user operation thanks to 3.5-inch colour touch screen
- Newly developed multi-position basket allows for numerous configuration options
- Fast and easy printing of PDF and JPEG file formats directly from USB memory stick
- Quick and easy Wi-Fi connectivity
- Minimised maintenance and production interruptions from high-capacity "hot swap" ink tanks
- Reliable performance and guaranteed colour consistency across every unit

PRODUCT RANGE





TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-6000

TECHNOLOGY

Nozzle Pitch

Printer Type

12 Colour 60"/1524mm Print Technology Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head \times 1 print head)

2,400 x 1200 dpi

Number of Nozzles 18,432 nozzles (1536 nozzles x 12 colour)

Line Accuracy ±0.1% or less

User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only

 $600\mbox{ dpi}\times2$ includes Non-firing nozzle detection and compensation system

minimum 4 pl per colour Ink Droplet Size Sales Ink: 160ml/330ml/700ml Ink Capacity Bundled Starter Ink: 330ml

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser Ink Type

Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11 OS Compatability

SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02) Printer Languages

Standard Interfaces

USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b Please refer to user manual how to activate/deactivate the wireless LAN

MEMORY

3 GB Standard memory 320 GB Hard Drive

PRINT TIME FOR AO PAGE SIZE

Media Type Print Mode: Print Time Print Mode Print Time Plain Paper Fast Standard 1:37 min 2:51 min

Print Mode Print Time Coated Paper Standard High Quality 2:51 min 5:36 min Print Mode Print Time

Glossy Photo Paper

MEDIA HANDLING

Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever) Media Feed and Output

Standard High Quality

203.2 mm

Media Width Roll paper: 203.2 -1524 mm Cut sheet: 203.2 - 1524 mm Roll/Cut: 0.07 - 0.8 mm Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

(Varies according to the OS and application) Cut sheet: 1.6 m

Margins Printable area

Media Feed Capacity

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply Power Consumption

Operating Environment

Accoustic Noise (Power/ Pressure)

Regulations

Enviroment Certificates

WHAT'S INCLUDED What's in the Box?

Software Included

OPTIONS Optional Items

CONSUMABLES User Replaceable Items Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

515mm (JIS B2), 728mm (JIS B1), 1030mm (JIS B0), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", 257mm (JIS B4)*, 297mm(ISO A3)*, 329mm (ISO A3)*, 329mm

 $\ensuremath{^{*}\text{Some}}$ environmental conditions may not produce the desired result

Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1999 x 984 x 1168 mm (Basket Open) 1999 x 766 x 1168 mm (Basket Closed) 167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

Printer (Main unit with pallet): 2227 x 915 x 1022 mm

210 kg Roll Unit: 2133 x 562 x 461 mm 40 kg

AC 100-240V (50-60Hz)

Operation: 103 W or less Sleep mode: 3.6W or less Default setting for the time to enter the Sleep mode:

Approx. 5 Minutes Power off: 0.3 W or less

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Operation: 50 dB (A) (Glossy paper, Print priority:

Standard) Standby: 35 dB (A) or less Operation: 6.7 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)

Europe: CE mark, Russia: EAC, Other countries: CB certification

International Energy Star Program (WW), RoHS

Printer, Roll Unit, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard Environment Leaflet, User Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.

2/3" Roll Holder: RH2-45

Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice." and R. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper)

compatibility list to see which variety of paper/media is recommended







Crystal-fidelity

Canon Inc.

Canon Europe canon-europe.com

English edition

© Canon Europa N.V.,2017

